

# PTFE Packing with Kynol Fiber Corners

Code: KXTP606



## Description

Braided from Kynol™ fiber and PTFE fiber. It contains the advantage both PTFE and kynol. It has good strength and lubricates.



Item no.: KXTP606

PTFE Packing with Kynol Fiber Corners

Item no.: KXTP606

- \* Clean packing
- \* High pressure conditions than using pure PTFE packings

## Typical Application

- \* Suited well where graphite impregnation not be acceptable
- \* For abrasive media, and where contamination is not permitted
- \* Chemical plants and pulp and paper mills
- \* Rotating and reciprocating pumps, washer journals, liquor pumps, refiners etc.

## Technical Data

Material	100% Kynol fiber and PTFE
Temperature Range	-200 up to +260 oC atmosphere
Rotating	20 bar
Reciprocating	100 bar
Static	200 bar
Shaft Speed	20 m/s in rotary
PH	1~13
Density	1.5g/cm <sup>3</sup>

Copyright © 2014-2015

Ningbo Kaxite Sealing Materials Co., Ltd.

No.134,Huancheng North Road,Jiangbei District,Ningbo City,Zhejiang Province,China (Zip:315020)

Website:<http://www.seal-china.com> E-mail:[sales@seal-china.com](mailto:sales@seal-china.com),[kaxite@seal-china.com](mailto:kaxite@seal-china.com)